

### Remote I/O Units



A Remote I/O Unit connects VersaMax I/O modules to a host PLC or computer via a variety of networks. This makes it easy to include VersaMax I/O in the innovative PROFINET interface, as well as Genius, PROFIBUS-DP, DeviceNet, or other Ethernet installations. Together, the Remote I/O Unit and its modules form an I/O station capable of providing up to 256 points of I/O.

	IC200PNS001	IC200PNS002	IC200DBI001	IC200EBI001
Product Name	Remote I/O PROFINET Network Interface Unit (Cooper Media) with built-in switch	Bus Transmitter Expansion Module (Fiber Media) with built-in switch	Remote I/O DeviceNet Network Interface Unit (Slave)	Remote I/O Ethernet Network Interface Unit
Lifecycle Status	Active	Active	Active	Active
Protocol Supported	PROFINET Slave, Version 2.2 Class A IO-Device	PROFINET Slave, Version 2.2 Class A IO-Device	DeviceNet Slave	EGD and Modbus TCP Server
Distance	100 Meters max. drop length 10/100Mbaud	2 – 2,000 (Full-Duplex) 2 – 400 (Half-Duplex)	500Kbps 100m bus length and branches totaling < 39m 250Kbps 250m bus length and branches totaling < 78m 125Kbps 500m bus length and branches totaling < 156m	100 Meters max. drop length 10/100Mbaud
I/O Discrete Points	2880 bytes total 1440 bytes of input data 1440 bytes of output data	2880 bytes total 1440 bytes of input data 1440 bytes of output data	Includes both discrete and analog. Up to 128 bytes of inputs + 2-byte status word Up to 128 bytes of outputs + 2-byte control word.	1024 bytes maximum both discrete and analog. %I: 2048 points %Q: 2048 points
I/O Analog Words	2880 bytes total 1440 bytes of input data 1440 bytes of output data	2880 bytes total 1440 bytes of input data 1440 bytes of output data	Includes both discrete and analog. Up to 128 bytes of inputs + 2-byte status word Up to 128 bytes of outputs + 2-byte control word.	1024 bytes maximum both discrete and analog. %AI: 128 channels %AQ: 128 channels
I/O Data	N/A	N/A	Up to 128 bytes of inputs + 2-byte status word Up to 128 bytes of outputs + 2-byte control word.	256 Bytes of input, output, Analog input and Analog output
I/O Data Update Rate	Configurable: 1ms, 2ms, 4ms, 8ms, 16ms, 32ms, 64ms, 128ms, 256ms and 512ms	Configurable: 1ms, 2ms, 4ms, 8ms, 16ms, 32ms, 64ms, 128ms, 256ms and 512ms	N/A	N/A
Network Topology	Daisy-chain/line, star, or ring (redundant media) topology.	Daisy-chain/line, star, or ring (redundant media) topology.	Linear bus (trunkline/dropline); power and signal on the same network cable	Network dependent
Transmission Media	10/100BASE-T	Fiber 100BASE-FX	Shielded, dual twisted pair cable, terminated at both ends	Ethernet twisted pair
Connector	(2) RJ45 with built-in switch	(2) SC or SC-Duplex with built-in switch	5-pin open pluggable connector	RJ-45
User Diagnostic Data	32 input status bits and 32 output control bits	32 input status bits and 32 output control bits	2 bytes of status/control	4
Number of Modules	8 per NIU/station, not expandable	8 per NIU/station, not expandable	8 per NIU/station	8 per NIU/station
Redundancy	No	No	N/A	No
5V Backplane Current Consumption (mA)	3 Watts	5 Watts	160	175
3.3V Backplane Current Consumption (mA)	N/A	N/A	10	425
Dimensions (W x H x D)	134mm (5.28 in) x 132mm (5.2 in)	134mm (5.28 in) x 132mm (5.2 in)	133.4 mm (5.25 in) x 85.9 mm (3.38 in) not including the height of power supply	133.4 mm (5.25 in) x 85.9 mm (3.38 in) not including the height of power supply