

TACH100 Standalone Digital Tachometer

Datasheet

Bently Nevada Machinery Condition Monitoring

176063 Rev. K



Description

The Bently Nevada TACH100_Digital_Tachometer can be used as a stand-alone unit for speed indication or in conjunction with any permanently installed monitoring system as a remote speed indicator. It is often used when a permanent monitoring system is located some distance away (e.g. in a control room) or when no permanent monitoring system is installed and speed indication is required at the machine.

The digital tachometer is a compact unit, containing its own power supply that can power a Proximitors sensor (-24 Vdc). The tachometer also accepts signal and common wires from an externally-powered Keyphasor Proximity Probe (such as may be available when a permanent monitoring system is installed). The wires can be connected in parallel with the Keyphasor input on the monitor rack or to the Keyphasor probe itself.

CE

Specifications

Inputs

Signal	From any Bently Nevada Proximator Sensor.
Threshold	Automatic adjustment.
Hysteresis	0.2 Vdc to 2.5Vdc, field-adjustable.
Events Per Turn	1 to 99, field-adjustable.
Electrical Supply	110–230 Vac, 50–60 Hz. 1.5 Amp, SB fuse. 1.01 Watts nominal power consumption with 88888 displayed.

Outputs

Display Type	6-digit LED, 7 segments per digit. Digit height is 13.2 mm (0.52 in)
Measurement Range	1 to 999,999 rpm.
Measurement Resolution	1 rpm
Measurement Accuracy	Accurate to within 0.015% of input speed displayed in RPM.
Display Hysteresis	Input signal must change by 0.003% minimum to display a new output value.
Proximator Power	–24 Vdc at 20 mA maximum.

Environmental Limits



For Indoor Use Only

Pollution Degree	2
Installation Category	II

Altitude	2000 m
Operating Temperature	0°C to +60°C (+32°F to +140°F)
Storage Temperature	–40°C to +85°C (–40°F to +185°F)
Relative Humidity	95% max, noncondensing

Physical Size

Height	76.2 mm (3 in)
Width	139.7 mm (5.5 in)
Depth	149.1 mm (5.8 in)
Weight	1.13 kg (2.5 lb)

Directives (CE and EMC)

CE Mark Directive

The TACH100_Digital_Tachometer has been tested and approved for installation within the European Union and European Environmental Agency regions. This device has been designed and tested to meet the following directives.

EMC Directives

Radiated Emissions	EN5501, Group 1 Class A
Conducted Emissions	EN5501, Group 1 Class A
EN61000–6–2 Electrostatic Discharge	IEC 61000–4–2, Criteria B
Radiated Susceptibility	IEC 61000–4–3, Criteria A
Electrical Fast Transient	IEC 61000–4–4, Criteria B
AC Power Surge Susceptibility	IEC 61000–4–5, Criteria B

AC Power Flicker Emissions	IEC 61000-3-3, Criteria A
RF Conducted Susceptibility	IEC 61000-4-6, Criteria A
Voltage Interrupt Susceptibility	IEC 61000-4-11, Criteria B
Voltage Dip Susceptibility	IEC 61000-4-11, Criteria A

EMC Standards

This product is tested to meet Council Directive 89/336/EEC Electromagnetic Compatibility (EMC) as last amended by EC Directive 93/68/EEC.

EN61000-6-4 Generic emission standard, Part 2, Industrial Environment. EN61000-6-2 EMC Generic Immunity standard, Part 2, Industrial Environment.

Certificate of Conformity

Registration Number: AE 72062927 0001